



NR035DB

CAPACITY IS IN POUNDS @ 24 INCH LOAD CENTER

EQUIPPED WITH 1.6" x 42" FORKS & SINGLE REACH CARRIAGE

RATINGS ARE PROVIDED FOR BOTH STANDARD CARRIAGE AND WITH INTEGRAL SIDESHIFTER

24 Volt 12.5" Battery Compartment Minimum Battery Weight - 1400 LBS.

I.D.	OALH	MFH	CAPACITY @ MFH		LIFT HEIGHT WITH MAX CAPACITY LOAD			
			w/o SS	INTEGRAL SS	w/o SS		INTEGRAL SIDESHIFTER	
			LOAD	LOAD CENTERED	LIFT HEIGHT	LOAD	LIFT HEIGHT	LOAD CENTERED
34"	87	191	3500	3500	191	3500	191	3500
	91	203	3500	3500	203	3500	203	3500
	95	212	3500	3500	212	3500	212	3500
	101	227	3500	3500	227	3500	227	3500
	107	242	3450	3350	240	3500	238	3500
	110	251	3150	3100	240	3500	238	3500
	119	272	2600	2550	239	3500	237	3500
38"	87	191	3500	3500	191	3500	191	3500
	91	203	3500	3500	203	3500	203	3500
	95	212	3500	3500	212	3500	212	3500
	101	227	3500	3500	227	3500	227	3500
	107	242	3500	3500	242	3500	242	3500
	110	251	3500	3450	251	3500	249	3500
	119	272	3100	3050	259	3500	256	3500
41"	87	191	3500	3500	191	3500	191	3500
	91	203	3500	3500	203	3500	203	3500
	95	212	3500	3500	212	3500	212	3500
	101	227	3500	3500	227	3500	227	3500
	107	242	3500	3500	242	3500	242	3500
	110	251	3500	3450	251	3500	249	3500
	119	272	3450	3350	269	3500	256	3500
42"	87	191	3500	3500	191	3500	191	3500
	91	203	3500	3500	203	3500	203	3500
	95	212	3500	3500	212	3500	212	3500
	101	227	3500	3500	227	3500	227	3500
	107	242	3500	3500	242	3500	242	3500
	110	251	3500	3450	251	3500	249	3500
	119	272	3450	3350	269	3500	256	3500

4/29/2013

NOTES:

Above capacities are with Standard 5" x 3.9" load wheels.

Contact Applications Engineering if you have any questions about the information above, or about a specific truck configuration.



NR035DB

CAPACITY IS IN POUNDS @ 24 INCH LOAD CENTER

EQUIPPED WITH 1.6" x 42" FORKS & SINGLE REACH CARRIAGE

RATINGS ARE PROVIDED FOR BOTH STANDARD CARRIAGE AND WITH INTEGRAL SIDESHIFTER

24/36 Volt 14.5" Battery Compartment Minimum Battery Weight - 1600 LBS.

I.D.	OALH	MFH	CAPACITY @ MFH		LIFT HEIGHT WITH MAX CAPACITY LOAD			
			w/o SS	INTEGRAL SS	w/o SS		INTEGRAL SIDESHIFTER	
			LOAD	LOAD (CENTERED)	LIFT HEIGHT	LOAD	LIFT HEIGHT	LOAD (CENTERED)
34"	87	191	3500	3500	191	3500	191	3500
	91	203	3500	3500	203	3500	203	3500
	95	212	3500	3500	212	3500	212	3500
	101	227	3500	3500	227	3500	227	3500
	107	242	3500	3500	242	3500	242	3500
	110	251	3300	3200	244	3500	241	3500
	119	272	2700	2650	243	3500	240	3500
38"	87	191	3500	3500	191	3500	191	3500
	91	203	3500	3500	203	3500	203	3500
	95	212	3500	3500	212	3500	212	3500
	101	227	3500	3500	227	3500	227	3500
	107	242	3500	3500	242	3500	242	3500
	110	251	3500	3500	251	3500	251	3500
	119	272	3250	3150	263	3500	260	3500
41"	87	191	3500	3500	191	3500	191	3500
	91	203	3500	3500	203	3500	203	3500
	95	212	3500	3500	212	3500	212	3500
	101	227	3500	3500	227	3500	227	3500
	107	242	3500	3500	242	3500	242	3500
	110	251	3500	3500	251	3500	251	3500
	119	272	3500	3500	272	3500	272	3500
42"	87	191	3500	3500	191	3500	191	3500
	91	203	3500	3500	203	3500	203	3500
	95	212	3500	3500	212	3500	212	3500
	101	227	3500	3500	227	3500	227	3500
	107	242	3500	3500	242	3500	242	3500
	110	251	3500	3500	251	3500	251	3500
	119	272	3500	3500	272	3500	272	3500

4/29/2013

NOTES:

Above capacities are with Standard 5" x 3.9" load wheels.

Contact Applications Engineering if you have any questions about the information above, or about a specific truck configuration.



NR035DB

CAPACITY IS IN POUNDS @ 24 INCH LOAD CENTER

EQUIPPED WITH 1.6" x 42" FORKS & SINGLE REACH CARRIAGE

RATINGS ARE PROVIDED FOR BOTH STANDARD CARRIAGE AND WITH INTEGRAL SIDESHIFTER

24/36 Volt 16.5" Battery Compartment Minimum Battery Weight - 1850 LBS.

I.D.	OALH	MFH	CAPACITY @ MFH		LIFT HEIGHT WITH MAX CAPACITY LOAD			
			w/o SS	INTEGRAL SS	w/o SS		INTEGRAL SIDESHIFTER	
			LOAD	LOAD (CENTERED)	LIFT HEIGHT	LOAD	LIFT HEIGHT	LOAD (CENTERED)
34"	87	191	3500	3500	191	3500	191	3500
	91	203	3500	3500	203	3500	203	3500
	95	212	3500	3500	212	3500	212	3500
	101	227	3500	3500	227	3500	227	3500
	107	242	3500	3500	242	3500	242	3500
	110	251	3450	3350	249	3500	247	3500
	119	272	2850	2800	248	3500	246	3500
38"	87	191	3500	3500	191	3500	191	3500
	91	203	3500	3500	203	3500	203	3500
	95	212	3500	3500	212	3500	212	3500
	101	227	3500	3500	227	3500	227	3500
	107	242	3500	3500	242	3500	242	3500
	110	251	3500	3500	251	3500	251	3500
	119	272	3350	3300	268	3500	266	3500
41"	87	191	3500	3500	191	3500	191	3500
	91	203	3500	3500	203	3500	203	3500
	95	212	3500	3500	212	3500	212	3500
	101	227	3500	3500	227	3500	227	3500
	107	242	3500	3500	242	3500	242	3500
	110	251	3500	3500	251	3500	251	3500
	119	272	3500	3500	272	3500	272	3500
42"	87	191	3500	3500	191	3500	191	3500
	91	203	3500	3500	203	3500	203	3500
	95	212	3500	3500	212	3500	212	3500
	101	227	3500	3500	227	3500	227	3500
	107	242	3500	3500	242	3500	242	3500
	110	251	3500	3500	251	3500	251	3500
	119	272	3500	3500	272	3500	272	3500

4/29/2013

NOTES:

Above capacities are with Standard 5" x 3.9" load wheels.

Contact Applications Engineering if you have any questions about the information above, or about a specific truck configuration.



NR040DB

CAPACITY IS IN POUNDS @ 24 INCH LOAD CENTER

EQUIPPED WITH 1.8" x 42" FORKS & SINGLE REACH CARRIAGE

RATINGS ARE PROVIDED FOR BOTH STANDARD CARRIAGE AND WITH INTEGRAL SIDESHIFTER

24 Volt 12.5" Battery Compartment Minimum Battery Weight - 1400 LBS.

I.D.	OALH	MFH	CAPACITY @ MFH		LIFT HEIGHT WITH MAX CAPACITY LOAD			
			w/o SS	INTEGRAL SS	w/o SS		INTEGRAL SIDESHIFTER	
			LOAD	LOAD (CENTERED)	LIFT HEIGHT	LOAD	LIFT HEIGHT	LOAD (CENTERED)
34"	87	191	3800	3700	166	4000	152	4000
	91	203	3700	3600	169	4000	155	4000
	95	212	3650	3600	171	4000	158	4000
	101	227	3650	3600	185	4000	173	4000
	107	242	3400	3350	189	4000	177	4000
	110	251	3150	3100	191	4000	179	4000
	119	272	2600	2550	199	4000	187	4000
38"	87	191	3800	3700	166	4000	152	4000
	91	203	3700	3600	169	4000	155	4000
	95	212	3650	3600	171	4000	158	4000
	101	227	3650	3600	185	4000	173	4000
	107	242	3600	3500	189	4000	177	4000
	110	251	3550	3450	191	4000	179	4000
	119	272	3100	3050	199	4000	187	4000
41"	87	191	3800	3700	166	4000	152	4000
	91	203	3700	3600	169	4000	155	4000
	95	212	3650	3600	171	4000	158	4000
	101	227	3650	3600	185	4000	173	4000
	107	242	3600	3500	189	4000	177	4000
	110	251	3550	3450	191	4000	179	4000
	119	272	3450	3350	199	4000	187	4000
42"	87	191	3800	3700	166	4000	152	4000
	91	203	3700	3600	169	4000	155	4000
	95	212	3650	3600	171	4000	158	4000
	101	227	3650	3600	185	4000	173	4000
	107	242	3600	3500	189	4000	177	4000
	110	251	3550	3450	191	4000	179	4000
	119	272	3450	3350	199	4000	187	4000

4/29/2013

NOTES:

Above capacities are with Standard 5" x 3.9" load wheels.

Contact Applications Engineering if you have any questions about the information above, or about a specific truck configuration.



NR040DB

CAPACITY IS IN POUNDS @ 24 INCH LOAD CENTER

EQUIPPED WITH 1.8" x 42" FORKS & SINGLE REACH CARRIAGE

RATINGS ARE PROVIDED FOR BOTH STANDARD CARRIAGE AND WITH INTEGRAL SIDESHIFTER

24/36 Volt 14.5" Battery Compartment Minimum Battery Weight - 1600 LBS.

I.D.	OALH	MFH	CAPACITY @ MFH		LIFT HEIGHT WITH MAX CAPACITY LOAD			
			w/o SS	INTEGRAL SS	w/o SS		INTEGRAL SIDESHIFTER	
			LOAD	LOAD (CENTERED)	LIFT HEIGHT	LOAD	LIFT HEIGHT	LOAD (CENTERED)
34"	87	191	3900	3800	183	4000	170	4000
	91	203	3850	3750	185	4000	172	4000
	95	212	3800	3700	188	4000	175	4000
	101	227	3800	3700	201	4000	189	4000
	107	242	3550	3450	205	4000	192	4000
	110	251	3250	3200	207	4000	194	4000
	119	272	2700	2650	214	4000	202	4000
38"	87	191	3900	3800	183	4000	170	4000
	91	203	3850	3750	185	4000	172	4000
	95	212	3800	3700	188	4000	175	4000
	101	227	3800	3700	201	4000	189	4000
	107	242	3700	3600	205	4000	192	4000
	110	251	3650	3550	207	4000	194	4000
	119	272	3250	3150	214	4000	202	4000
41"	87	191	3900	3800	183	4000	170	4000
	91	203	3850	3750	185	4000	172	4000
	95	212	3800	3700	188	4000	175	4000
	101	227	3800	3700	201	4000	189	4000
	107	242	3700	3600	205	4000	192	4000
	110	251	3650	3550	207	4000	194	4000
	119	272	3550	3450	214	4000	202	4000
42"	87	191	3900	3800	183	4000	170	4000
	91	203	3850	3750	185	4000	172	4000
	95	212	3800	3700	188	4000	175	4000
	101	227	3800	3700	201	4000	189	4000
	107	242	3700	3600	205	4000	192	4000
	110	251	3650	3550	207	4000	194	4000
	119	272	3550	3450	214	4000	202	4000

4/29/2013

NOTES:

Above capacities are with Standard 5" x 3.9" load wheels.

Contact Applications Engineering if you have any questions about the information above, or about a specific truck configuration.



NR040DB

CAPACITY IS IN POUNDS @ 24 INCH LOAD CENTER

EQUIPPED WITH 1.8" x 42" FORKS & SINGLE REACH CARRIAGE

RATINGS ARE PROVIDED FOR BOTH STANDARD CARRIAGE AND WITH INTEGRAL SIDESHIFTER

24/36 Volt 16.5" Battery Compartment Minimum Battery Weight - 1850 LBS.

I.D.	OALH	MFH	CAPACITY @ MFH		LIFT HEIGHT WITH MAX CAPACITY LOAD			
			w/o SS	INTEGRAL SS	w/o SS		INTEGRAL SIDESHIFTER	
			LOAD	LOAD (CENTERED)	LIFT HEIGHT	LOAD	LIFT HEIGHT	LOAD (CENTERED)
34"	87	191	4000	3800	191	4000	170	4000
	91	203	4000	3750	203	4000	172	4000
	95	212	4000	3700	212	4000	175	4000
	101	227	4000	3700	227	4000	189	4000
	107	242	4000	3450	242	4000	192	4000
	110	251	3950	3200	249	4000	194	4000
	119	272	3350	2650	251	4000	202	4000
38"	87	191	4000	3800	191	4000	170	4000
	91	203	4000	3750	203	4000	172	4000
	95	212	4000	3700	212	4000	175	4000
	101	227	4000	3700	227	4000	189	4000
	107	242	4000	3600	242	4000	192	4000
	110	251	3950	3550	249	4000	194	4000
	119	272	3350	3150	251	4000	202	4000
41"	87	191	4000	3800	191	4000	170	4000
	91	203	4000	3750	203	4000	172	4000
	95	212	4000	3700	212	4000	175	4000
	101	227	4000	3700	227	4000	189	4000
	107	242	4000	3600	242	4000	192	4000
	110	251	3950	3550	249	4000	194	4000
	119	272	3800	3450	256	4000	202	4000
42"	87	191	4000	3800	191	4000	170	4000
	91	203	4000	3750	203	4000	172	4000
	95	212	4000	3700	212	4000	175	4000
	101	227	4000	3700	227	4000	189	4000
	107	242	4000	3600	242	4000	192	4000
	110	251	3950	3550	249	4000	194	4000
	119	272	3850	3450	256	4000	202	4000

4/29/2013

NOTES:

Above capacities are with Standard 5" x 3.9" load wheels.

Contact Applications Engineering if you have any questions about the information above, or about a specific truck configuration.



NDR030DB

CAPACITY IS IN POUNDS @ 24 INCH LOAD CENTER

EQUIPPED WITH 1.6" x 42" FORKS & DOUBLE REACH CARRIAGE

RATINGS ARE PROVIDED FOR STANDARD CARRIAGE WITH INTEGRAL SIDESHIFTER

36 Volt 14.5" Battery Compartment Minimum Battery Weight - 1600 LBS.

I.D.	OALH	MFH	CAPACITY @ MFH	LIFT HEIGHT WITH MAX CAPACITY LOAD	
			INTEGRAL SS	INTEGRAL SIDESHIFTER	
			LOAD CENTERED	LIFT HEIGHT	LOAD CENTERED
34"	87	191	2900	181	3000
	91	203	2900	185	3000
	95	212	2850	188	3000
	101	227	2850	206	3000
	107	242	2800	212	3000
	110	251	2600	214	3000
	119	272	2150	224	3000
38"	87	191	2900	181	3000
	91	203	2900	185	3000
	95	212	2850	188	3000
	101	227	2850	206	3000
	107	242	2800	212	3000
	110	251	2800	214	3000
	119	272	2550	224	3000
41"	87	191	2900	181	3000
	91	203	2900	185	3000
	95	212	2850	188	3000
	101	227	2850	206	3000
	107	242	2800	212	3000
	110	251	2800	214	3000
	119	272	2750	224	3000
42"	87	191	2900	181	3000
	91	203	2900	185	3000
	95	212	2850	188	3000
	101	227	2850	206	3000
	107	242	2800	212	3000
	110	251	2800	214	3000
	119	272	2750	224	3000

4/29/2013

NOTES:

Above capacities are with Standard 5" x 2.9" load wheels.

Contact Applications Engineering if you have any questions about the information above, or about a specific truck configuration.



NDR030DB

CAPACITY IS IN POUNDS @ 24 INCH LOAD CENTER

EQUIPPED WITH 1.6" x 42" FORKS & DOUBLE REACH CARRIAGE

RATINGS ARE PROVIDED FOR STANDARD CARRIAGE WITH INTEGRAL SIDESHIFTER

36 Volt 16.5" Battery Compartment Minimum Battery Weight - 1850 LBS.

I.D.	OALH	MFH	CAPACITY @ MFH	LIFT HEIGHT WITH MAX CAPACITY LOAD	
			INTEGRAL SS	INTEGRAL SIDESHIFTER	
			LOAD CENTERED	LIFT HEIGHT	LOAD CENTERED
34"	87	191	3000	191	3000
	91	203	3000	203	3000
	95	212	3000	212	3000
	101	227	3000	227	3000
	107	242	2950	242	3000
	110	251	2750	241	3000
	119	272	2250	240	3000
38"	87	191	3000	191	3000
	91	203	3000	203	3000
	95	212	3000	212	3000
	101	227	3000	227	3000
	107	242	3000	242	3000
	110	251	3000	251	3000
	119	272	2700	260	3000
41"	87	191	3000	191	3000
	91	203	3000	203	3000
	95	212	3000	212	3000
	101	227	3000	227	3000
	107	242	3000	242	3000
	110	251	3000	251	3000
	119	272	3000	272	3000
42"	87	191	3000	191	3000
	91	203	3000	203	3000
	95	212	3000	212	3000
	101	227	3000	227	3000
	107	242	3000	242	3000
	110	251	3000	251	3000
	119	272	3000	272	3000

4/29/2013

NOTES:

Above capacities are with Standard 5" x 2.9" load wheels.

Contact Applications Engineering if you have any questions about the information above, or about a specific truck configuration.